

Modern Vintage & Modern Vintage Chic - Datasheet					
		Standard requirement	Test result		
Product specifications			Pass		
Total thickness	EN ISO 24346	2,5 mm	✓	-	
Thickness of wear layer	EN ISO 24340	0,55 mm	✓	-	
Weight	EN ISO 23997	4,400 g/m2	✓	-	
Side length, delivery form	EN ISO 24342	-	✓	Modern Vintage Size 304.8 x 76.2 mm Carton 144 planks = 3.34 m2	Modern Vintage Chic 720 x 144 mm 32 planks = 3.32 m2
Classification & Certification					
Type of flooring	EN ISO 10582	Heterogeneous, PVC	✓	-	
Classification	EN ISO 10874	22/33/42, 31/34/43	✓	-	
Burning behaviour	EN 13501-1/ EN ISO 9239-1/ 11925-2 EN 14041: 2004/AC:2006	Bfl-s1	✓	Bfl-s1	
Slip resistance	DIN 51130/ EN 13893 EN 14041: 2004/AC:2006	R9, DS	✓	R9, DS	
Declaration of Performance	-	-	-	No. GFL GD – DoP - 018	
Technical properties					
Abrasion resistance	EN ISO 10582	-	✓	Class T	
Dimension stability	EN ISO 23999	< 0.25%	✓	< 0.05 %	
Squareness & straightness	EN ISO 24342	< 0.35 mm tolerance	✓	< 0.20 mm	
Curling after exposure to heat	EN ISO 23999	< 2 mm	✓	0 mm	
Residual indentation	EN ISO 24343-1	< 0.1 mm	✓	0.05 mm	
Castor wheel chair	ISO 4918	25,000 revolutions	✓	suitable, type W	
Flexibility	EN ISO 24344	20 mm no crack	✓	< 10 mm no crack	
Surface treatment	-	-	-	Top Protection Plus, PUR	
Color fastness	EN ISO 105-B02	≥ 6	✓	> 6	
Staining & resistance to chemicals Caustic soda solution (25%), Citric acid (10%), Acetone, Coffee (120g/l)	EN ISO 26987	-	✓	Index 0, excellent	
Thermal resistance	EN ISO 8302	-	✓	0.019 m2 K/W	
Underfloor heating	-	-	✓	suitable, max. 27°C	
Environment / Indoor air quality					
Formaldehyde emissions	EN 14041: 2004/AC:2006	-	✓		
Pentachlorophenol content	EN 14041: 2004/AC:2006	-	✓		
TVOC after 28 days	ISO 16000	-	✓	certified A+ (ÖTI report No. 71745)	
REACH	Regulation (EU) No. 1907/2006	in conformity	✓	no SVHC (Centexbel report No. 14.01560.02)	







*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle allant de A+ (très faibles émissions) à C (fortes émissions)





SCS Global Services